PRODUCT BRIEFING



Pack of 100 - I-Code 2 Card



I-Code 2 cards offer the popular Philips RFID chip embedded in a standard card. Operating according to the ISO 15693 standard, the I-Code family provide long-range wireless read/write functionality at 13.56 MHz for applications such as article tracking and supply chain management.

I-Code 2 cards can operate at around 1.5 m depending on the reader power, and provide 28 blocks of 4 bytes data storage, with 5 year data retention and 100,000 write cycle endurance.

Supplied as blank white PVC cards to ISO standard in packs of 100.

Limited stock remaining

Contactless card suitable for multiple application types. 28 blocks of 4 bytes memory. Operates at 13.56 MHz. Pack of 100 cards.

To buy, visit:

https://www.smartcardfocus.com/shop/ilp/id~952/p/index.shtml

This Product Briefing has been produced by <u>Dot Origin Ltd</u>, the smart card experts behind <u>SmartcardFocus.com</u>. If you have a query email <u>sales@smartcardfocus.com</u> or call us on +44 (0)1428 685250.

PRODUCT BRIEFING ©2022 DOT ORIGIN LTD PAGE 1 OF 2

I-Code 2

Technical Specifications

Contactless transmission of data and supply energy (no battery needed)

Operating distance: up to 1.5m Operating frequency: 13.56MHz Fast data transfer: up to 53 kbit/s

High data integrity: 16-bit CRC, framing

Data retention: 5 years

Endurance: 100 000 cycles

Security Features: Lock mechanism for each user memory block (write protection)
Supported Standards: EPCglobal Inc., 13.56MHz ISM Band Class 1 Radio Frequency

Identification Tag Interface Specification

Manufacturer: NXP

PRODUCT BRIEFING ©2022 DOT ORIGIN LTD PAGE 2 OF 2